

PRE'CON MAKE ATMOSPHERIC VENTS MODEL 2054

DESCRIPTION:

Open Atmospheric Vents are installed on the top of vent pipes from underground or above ground fuel storage tanks. The vent cap and internal wire screen are designed to protect the tank vent lines against intrusion and blockage from water, debris or insects. These vents are always open to atmosphere and allow any pressure or vacuum into the tank to vent.

Features

- * Reliable Service – vent cap drain spouts extend outward to stop rainwater entry.
- * Corrosion-Resistant Construction – aluminum body and cap assure a long service life.
- * Easy Installation – Model 2054 is available in 1.1/ 2" upto 3" threaded that provide for attachment to the vent line.
- * Slip on Model with set screw available on option.
- * High-Maximum Flow Rate – 7000 SCFH at 2 psig.
- * 40-Mesh Brass Wire Screen – Helps prevent debris and insects from entering the tank vent lines.

Code Compliance:

When properly sized for the tank, this vent will comply with NFPA 30 Requirements – for venting gasoline vapors upward
—UL-142, UL2085, UL-2244;

Material

Body: Aluminum
Screen: 40-mesh brass
Set Screws: Brass

Application

The PRECON Open vents vapors downward and is used primarily on diesel, fuel oil, wasteoil and motor-oil tanks, but can also be used on a wide variety of above ground storage tank venting applications.

